



A U S T R A L I A

AEM Australia Pty. Ltd.  
ABN 76 003 136 383

Quality  
Endorsed  
Company  
ISO 9001:2000  
Lic. No. 0807  
Standards Australia

## ***M.V. Side Break Switch Type "SB"***



<b>Rated Voltage:</b>	12/24kV to 36kV
<b>Rated Current:</b>	800A
<b>BIL Rating:</b>	150kVp & 200kVp
<b>Current Withstand:</b>	25kA/1 sec

# M.V. Side Break Switch Type "SB"

## General Description

The AEM Type "SB" is a 3 phase Side Break Switch designed for MV Outdoor Distribution Systems to comply with AS1306-1985 and IEC 129.

## Features

- Current carrying parts are manufactured from HD. HC. Copper.
- Silver Plated contacts for high performance, low maintenance and long operational life.
- Terminal Palms are bright tin plated for use with copper and aluminium connectors.
- Adjustable phase centres.
- Load Break Devices.

## Options

- Light Weight Design.
- Coastal Design.
- Pre-assembled or Modular Delivery.
- Mounting: Pole Top, Mid Pole and Vertical.
- Flicker Arcing Horns.
- Insulators: Porcelain, Polymeric.
- Pole Type: Timber, Metal, Concrete.
- Crossarms: Aluminium, Steel, Timber, Insulated.

## Operation

- Rotary handle.
- Up Down Handle.
- Operating Stick.

