



A U S T R A L I A

Quality
Endorsed
Company
ISO 9001:1994
Lic. No. 0807
Standards Australia

AEM Australia Pty. Ltd.
ABN 76 003 136 383

M.V. Side Break Switch Type "ST"



Disconnecter

Rated Voltage:	12/24kV & 36kV
Rated Current:	800A
BIL Rating:	150kVp & 200 kVp
Current Withstand:	25kA/3 sec

M.V. Side Break Switch Type "ST"

General Description

The AEM Type "ST" Switch is a 3 phase Side Break Switch designed for MV Outdoor Distribution Systems to comply with: AS 1306-1985 and IEC 129.

Features

- Current carrying parts are manufactured from HD. HC. Copper.
- Silver Plated contacts for high performance, low maintenance and long operational life.
- Terminal Palms are bright tin plated for use with copper and aluminium connectors.
- Hinge End Contact Blade so that current path is not through pivot joint.
- Load Break Interrupters.
- Adjustable Phase Centres.

Options

- Mounting: Pole Top, Mid Pole and Vertical.
- Interphase Shaft Steel or Insulated.
- Insulators: Porcelain, Polymeric.
- Pole Type: Timber, Metal, Concrete.
- Crossarms : Timber, Steel or Insulated.

Operation

- Rotary Handle.
- Up Down Handle.
- Operating Stick.

